

### AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

#### Listing of Claims:

Claim 1 (Currently Amended): An image processing apparatus comprising:

~~a communication unit for communicating with an information processing apparatus having a function of operating image information;~~

~~a storage for storing first image information which represents at least one element in a compressed format therein; and~~

~~a controller for sending second image information which represents the at least one element to the information processing apparatus, the amount of the second image information being smaller than that of the first image information, acquiring result information representing an operation which is executed for the sent second image information on the information processing apparatus, editing the first image information according to the acquired result information in an intermediate process where the first image information stored in the storage is expanded, and sending the edited first image information in the compressed format to the information processing apparatus~~

a communication unit configured to communicate with an information processing apparatus, the information processing apparatus configured to operate on image information;

a storage configured to store first image information which represents at least one element; and

a controller configured to send second image information to the information processing apparatus, said second image information represents the at least one element and an amount of the second image information is smaller than an amount of the first image information, wherein

the controller is further configured to acquire result information from an operation which is executed for the sent second image information on the information processing apparatus, the result information includes order information indicating an order of the images in a direction perpendicular to a display screen;

the controller is further configured to edit the first image information, wherein the first image information stored in the storage is expanded, the first image information is edited according to the acquired result information including the order information, so that if at least two elements superimpose each other, a portion of the image information covered by an element of higher order is not included by the edited first image information; and

the controller is further configured to send the edited first image information to the information processing apparatus.

Claim 2 (Currently Amended): The image processing apparatus according to claim 1, wherein the controller is further configured to execute ~~executes~~ at least one of a moving process, an enlargement process, a reduction process, and a deletion process on the at least one element ~~elements~~ during said editing of ~~to edit~~ the first image information ~~in the intermediate process.~~

Claim 3 (Cancelled).

Claim 4 (Currently Amended): The image processing apparatus according to claim 1, wherein a network is configured ~~provided~~ to connect among the image processing apparatus, the information processing apparatus and other information processing apparatuses, and

the controller is further configured to broadcast ~~broadcasts~~ the first image information which is edited and composed to a plurality of desired information processing apparatuses of the information processing apparatus and the other information processing apparatuses.

Claim 5 (Original): The image processing apparatus according to claim 4, wherein the network comprises a satellite communication network.

Claim 6 (Currently Amended): An image processing apparatus comprising:  
a communication unit configured to communicate ~~for communicating~~ with an information processing apparatus configured to process ~~which processes~~ first image information and second image information in association with each other, both of the first image information and the second image information representing at least one element and ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information;

an image processor configured to receive ~~for receiving~~ the second image information from the information processing apparatus via the communication unit, configured to display ~~displaying~~ the received second image information on a given display device, configured to receive ~~receiving~~ an operation instruction for the displayed second image information, configured to process ~~processing~~ the displayed second image information according to the operation instruction, and configured to send ~~sending~~ result information representing the processed and displayed second image information to the information processing apparatus;  
and

an output controller configured to receive ~~for receiving~~ the first image information via the communication unit, ~~which~~ the first image information being is edited according to the

result information on the information processing apparatus, and configured to cause ~~causing~~ a given printing device to print the received first image information, and

wherein when the operation instruction includes adding process for adding additional information to the displayed second image information, the image processor saves the additional information, and the output controller executes a superimpose process for the received first image information and the saved additional information and causes the given printing device to print a result of the superimpose process.

Claim 7 (Cancelled).

Claim 8 (Currently Amended): An image processing method applied to an image processing apparatus including having a communication unit configured to communicate ~~for communicating~~ with an information processing apparatus and a storage configured to store ~~for storing~~ first image information which represents at least one element ~~in a compressed format therein~~, the information processing apparatus ~~having a function of operating~~ configured to operate on image information, the method comprising the steps of:

sending second image information which represents the at least one element to the information processing apparatus, ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information;

acquiring result information ~~representing from~~ from an operation which is executed for the sent second image information on the information processing apparatus, wherein the result information includes order information indicating an order of the images in a direction perpendicular to a display screen;

editing the first image information according to the acquired result information including the order information, so that if at least two elements superimpose each other, a

portion of the image information covered by an element of higher order is not included by the edited first image information in an intermediate process where the first image information stored in the storage is expanded; and

sending the edited first image information ~~in the compressed format~~ to the information processing apparatus.

Claim 9 (Currently Amended): The image processing method according to claim 8, wherein the editing the first image information ~~step~~ includes a ~~substep of~~ executing at least one of a moving process, an enlargement process, a reduction process, and a deletion process on the at least one element ~~elements~~ to edit the first image information ~~in the intermediate process~~.

Claim 10 (Cancelled).

Claim 11 (Currently Amended): An image processing method applied to an image processing apparatus including ~~having~~ a communication unit for communicating with an information processing apparatus ~~having a function of processing~~ configured to process first image information and second image information in association with each other, both of the first information and the second image information representing at least one element and ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information; the method comprising ~~the steps of:~~

receiving the second image information from the information processing apparatus via the communication unit;

displaying the received second image information on a given display device;

receiving an operation instruction for the displayed second image information;

processing the displayed second image information according to the operation instruction;

sending result information representing the processed and displayed second image information to the information processing apparatus;

receiving the first image information via the communication unit, ~~which~~ the first image information being is edited according to the result information on the information processing apparatus; ~~and~~

~~causing a given printing device to print the received first image information~~  
saving an additional information, if the operation instruction includes an adding process for the adding additional information to the displayed second image information;

executing a superimpose process for the received first image information and the saved additional information; and

causing a given printing device to print at least one of the received first image information a result of the superimpose process.

Claim 12 (Cancelled).

Claim 13 (Currently Amended): An image information distributing method applied to a network system including a first image processing apparatus and a second image processing apparatus, the first image processing apparatus and the second image processing apparatus being interconnected with each other, the first image processing apparatus configured to store ~~storing~~ first image information ~~in a compressed format~~ and second image information, both of the first image information and the second image information representing at least one element, ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information, the method comprising ~~the steps of:~~

sending the second image information to the second image processing apparatus from the first image processing apparatus;

displaying the second image information on a given display device of the second image processing apparatus;

receiving an operation instruction for the displayed second image information in the second image processing apparatus;

processing the displayed second image information according to the operation instruction in the second image processing apparatus;

sending result information representing the processed and displayed second image information to the first image processing apparatus from the second image processing apparatus, wherein when the operation instruction includes adding process for adding additional information to the displayed second image information, wherein the additional information is saved in the second image processing apparatus;

editing the first image information, in the first image processing apparatus, according to the result information ~~in an intermediate process where the first image information stored in the storage is expanded;~~

sending the edited first image information ~~in the compressed format~~ to the second image processing apparatus from the first image processing apparatus; ~~and~~

executing a superimpose process for the received first image information and the saved additional information in the second image processing apparatus; and

causing a given printing device of the second image processing apparatus to print ~~the first image information sent from the first image processing apparatus~~ a result of the superimpose process.

Claim 14 (Currently Amended): The image information distributing method according to claim 13, wherein the network system includes other image processing apparatuses, and the sending of the edited first image information ~~sending step~~ includes a ~~substep of~~ broadcasting the first image information which is edited and composed to a plurality of desired information processing apparatuses of the second image processing apparatus and the other image processing apparatuses.

Claim 15 (Currently Amended): A storage medium ~~having~~ including computer readable program code means embodied in the medium, the storage medium being applicable to a computer including ~~having~~ a communication unit configured to communicate ~~for communicating~~ with an apparatus and a storage configured to store ~~for storing~~ first image information which represents at least one element ~~in a compressed format therein~~, the apparatus ~~having a function of operating~~ configured to operate on image information, the computer readable program code means comprising:

computer readable program code means for sending second image information which represents the at least one element to the apparatus, ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information;

computer readable program code means for acquiring result information representing an operation which is executed for the sent second image information on the apparatus, wherein definition information including order information is acquired as said result information, said order information indicating an order of the images in a direction perpendicular to a display screen;

computer readable program code means for editing the first image information according to the acquired result information ~~in an intermediate process where the first image information stored in the storage is expanded~~ wherein said first image information is edited



according to the order information so that when a plurality of elements superimpose each other, the portion of the image information covered by an element of higher order is not included by the edited first image information; and

computer readable program code means for sending the edited first image information ~~in the compressed format~~ to the apparatus.

Claim 16 (Currently Amended): A storage medium including ~~having~~ computer readable program code means embodied in the medium, the storage medium being applicable to a computer ~~having~~ including a communication unit for communicating with an apparatus ~~having a function of processing~~ configured to process first image information and second image information in association with each other, both of the first image information and the second image information representing at least one element, ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information, the computer readable program code means comprising:

computer readable program code means for receiving the second image information from the apparatus via the communication unit;

computer readable program code means for displaying the received second image information on a given display device;

computer readable program code means for receiving an operation instruction for the displayed second image information;

computer readable program code means for processing the displayed second image information according to the operation instruction;

computer readable program code means for sending result information representing the processed and displayed second image information to the apparatus;

computer readable program code means for saving additional information when the operation instruction includes adding process for adding the additional information to the displayed second image information;

computer readable program code means for receiving the first image information via the communication unit, ~~which is~~ the first image information being edited according to the result information on the apparatus; and

computer readable program code means for executing a superimpose process for the received first image information and the saved additional information; and

computer readable program code means for causing a given printing device to print ~~the received first image information~~ a result of the superimpose process.

Claims 17-20 (Cancelled):

Claim 21 (Currently Amended): An image processing apparatus comprising:

~~a communication unit for communicating with an information processing apparatus having a function of operating image information;~~

~~a storage for storing first image information which represents at least one element;~~  
and

~~a controller for sending second image information which represents the at least one element to the information processing apparatus, the amount of the second image information being smaller than that of the first image information, acquiring result information representing an operation which is executed for the sent second image information on the information processing apparatus, editing the first image information according to the acquired result information, and sending the edited first image information to the information processing apparatus~~

a communication unit configured to communicate with an information processing apparatus, wherein the information processing apparatus is configured to operate on image information;

a storage configured to store first image information which represents at least one element; and

a controller configured to send second image information to the information processing apparatus, said second image information represents the at least one element and an amount of the second image information is smaller than an amount of the first image information, wherein

the controller is further configured to acquire result information from an operation which is executed for the sent second image information on the information processing apparatus, the result information includes order information indicating an order of the images in a direction perpendicular to a display screen;

the controller is further configured to edit the first image information according to the acquired result information including the order information, so that if at least two elements superimpose each other, a portion of the image information covered by an element of higher order is not included by the edited first image information; and

the controller is further configured to send the edited first image information to the information processing apparatus.

Claim 22 (Original): The image processing apparatus according to claim 21, wherein the result information represents identification of the at least one elements and each location thereof.

Claim 23 (Currently Amended): An image processing method applied to an image processing apparatus including having a communication unit configured to communicate for communicating with an information processing apparatus and a storage configured to store for storing first image information which represents at least one element, the information processing apparatus configured to operate having a function of operating image information, the method comprising ~~the steps of~~:

sending second image information which represents the at least one element to the information processing apparatus, ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information;

acquiring result information representing an operation which is executed for the sent second image information on the information processing apparatus, wherein order information is included in said result information, and the order information indicates an order of the images in a direction perpendicular to a display screen;

editing the first image information according to the acquired result information, wherein said first image information is edited according to the order information so that when a plurality of elements superimpose each other, a portion of the image information covered by an element of higher order is not included by the edited first image information; and

sending the edited first image information to the information processing apparatus.

Claim 24 (Original): The image processing method according to claim 23, wherein the result information represents identification of the at least one elements and each location thereof.

Claim 25 (Currently Amended): An image information distributing method applied to a network system including a first image processing apparatus and a second image processing

apparatus, the first image processing apparatus and the second image processing apparatus being interconnected with each other, the first image processing apparatus configured to store ~~storing~~ first image information and second image information, both of the first image information and the second image information representing at least one element, ~~the~~ an amount of the second image information being smaller than ~~that~~ an amount of the first image information, the method comprising ~~the steps of:~~

sending the second image information to the second image processing apparatus from the first image processing apparatus;

displaying the second image information on a given display device of the second image processing apparatus;

receiving an operation instruction for the displayed second image information in the second image processing apparatus;

processing the displayed second image information according to the operation instruction in the second image processing apparatus;

sending result information representing the processed and displayed second image information to the first image processing apparatus from the second image processing apparatus, wherein when the operation instruction includes adding process for adding additional information to the displayed second image information, the additional information is saved in the second image processing apparatus;

editing the first image information, in the first image processing apparatus, according to the result information;

sending the edited first image information to the second image processing apparatus from the first image processing apparatus; ~~and~~

executing a superimpose process for the received first image information and the saved additional information in the second image processing apparatus; and

causing a given printing device of the second image processing apparatus to print the ~~first image information sent from the first image processing apparatus~~ a result of the superimpose process.